



RED LEAD PRIMER

General Description:

RED LEAD PRIMER is formulated based on modified alkyd and red lead pigment. It has an anti – corrosive property to prevent rust formation in ferrous surface such as steel structures.

Advantages and Uses:

- Anti corrosion
- Weather resistance for exterior surfaces.
- Good flow and brushability.
- Easy to apply.
- Excellent build and adhesion coat in alkyd system.

Characteristics and Physical Properties:

Colour	Red Orange
Coverage	13 – 15 m ² / lit.
Flash Point	39 ⁰ C
Solid Content	Approx 54% by volume
Recommended D.F.T	30 microns / coat.
Touch Dry	After 2 hrs.
Over coating	min. 12 hrs.
Shelf Life	one(1)year in cool place.

Application procedure:

- Substrate must be free from rust, dirt, oil and other contaminants.
- Sandblasting is required, if sandblasting is not possible manual wire brushing is recommended.

The above information is given to the best of our knowledge based on laboratory test and practical experience. However, as the paint is often used under condition beyond our control, we cannot guarantee anything but the quality of the paint itself. We reserve the right to change the given data without prior notice.

- Use deruster to remove away rust and rinse with water and let it dry. Apply 1 – 2 coats of RED LEAD PRIMER by roller, brush or spray.

Storage:

RED LEAD PRIMER should be kept in a cool area below 25⁰C. Keep in tightly closed container.

Cleaning of Tools:

All tools should be cleaned with Wash Thinner or PU Thinner # 155 as soon as possible.

Packing:

Available in 4 lit. (Usg), 20 lit. (Pail) and 200 lit. (Drum)

Physiological Hazards:

RED LEAD PRIMER does not contain dangerous solvents, nevertheless, good ventilation in working rooms is recommended as well as the use of safety tools and equipment. RED LEAD PRIMER is flammable and harmful if swallowed. If contact with eyes or skin occurs, wash well with fresh water and seek immediate medical advise.

FACTORY : P.O. BOX NO: 23085, SAJJAH INDUSTRIAL AREA, SHARJAH, U.A.E
TEL : 06 – 5311777, FAX 06 - 5311330:
SHOWROOM : P.O. BOX NO: 23085, INDUSTRIAL AREA, SHARJAH, U.A.E
TEL : 06 – 5328533, FAX 06 - 5328610
Website : <http://www.maspaints.com/> Email : masuae@emirates.net.ae



D-111/2004