



RED OXIDE PRIMER

General Description:

A primer with high adhesion based on modified alkyd resin and red iron oxide pigment. Ideal primer to ferrous surfaces such as steel, G.I. sheets and the likes.

Advantages:

- Good anti corrosive properties
- Excellent adhesion to metal surfaces.
- Good flexibility
- Good hiding capacity
- Ideal for interior and exterior surfaces.

Characteristics and Physical Properties:

Colour	Red
Coverage	13 – 15 m ² / lit.
Flash Point	39 ⁰ C
Solid Content	Approx 54% by volume
Recommended	35 microns / coat.

Drying Time:

Touch Dry	After 2 hrs.
Over coating	min. 12 hrs.
Shelf Life	One (1) year in cool place.

Application procedure:

- Substrate must be free from rust, dirt, oil and other contaminants. Sandblasting is required if sandblasting is not possible manual wire brushing is recommended. Use deruster to remove away rust and rinse with water and let it dry.

The above information is given to the best of our knowledge based on laboratory test and practical experience. However, as the paint is often used under condition beyond our control, we cannot guarantee anything but the quality of the paint itself. We reserve the right to change the given data without prior notice.

Method of Application: By brush, roller and Conventional Spray

Spray Data	
Conventional Spray	
Nozzle Orifice	2 – 3mm.
Nozzle Pressure	43 – 57 psi.
Dilution	10 – 15 %
Thinner	# 155

Storage:

RED OXIDE PRIMER should be kept in a cool area below 25⁰C. Keep in tightly closed container.

Cleaning of Tools:

All tools should be cleaned with Wash Thinner or Thinner # 155 as soon as possible.

Packing:

Available in 4 lit. (Usg), 20 lit. (Pail) and 200 lit. (Drum)

Physiological Hazards:

RED OXIDE PRIMER does not contain dangerous solvents, nevertheless, good ventilation in working rooms is recommended as well as the use of safety tools and equipment. RED OXIDE PRIMER is flammable and harmful if swallowed. If contact with eyes or skin occurs, wash well with fresh water and seek immediate medical advise.

FACTORY : P.O. BOX NO: 23085, SAJJAH INDUSTRIAL AREA, SHARJAH, U.A.E
TEL : 06 – 5311777, FAX 06 - 5311330:
SHOWROOM : P.O. BOX NO: 23085, INDUSTRIAL AREA, SHARJAH, U.A.E
TEL : 06 – 5328533, FAX 06 - 5328610
Website : <http://www.maspaints.com/> Email : masuae@emirates.net.ae



D-111/2004