



# WOOD PRESERVATIVE

## General Description:

WOOD PRESERVATIVE is a clear impregnating varnish with deep penetrations on wood to protect against fungus, termites and other insects.

## Major Uses:

Ideal for use in fencing, gates, portable out buildings, joinery, door, window frames, cladding in gardens, as well as roof timbers, hard wood, floor boards and as insect killer in furniture.

## Characteristics and Physical Properties:

Color	Transparent and colored -liquid
Specific Gravity	0.850
Flash Point	40 <sup>0</sup> C
Viscosity	17 sec. F.C # 4
% Solid Content	20

## Application Details:

Method of application	By brush , Spray.
Mixing Ratio	Single Pack
Thinner / Cleaner	Thinner # 155

## Surface Preparation:

- Surface must be clean, dry, free from dirt, oil, grease and other foreign matters. If detergent is used for cleaning, rinse with fresh water.
- The temperature of the substrate should be min 5<sup>0</sup> C, above the dew point. Avoid painting on direct sunlight.
- Apply wood preservative at a rate of 6 – 8 m<sup>2</sup> on softwood and 10 – 14 m<sup>2</sup> / lit. for hardwood.

## Drying Time:

Dry touch @ 25 <sup>0</sup> C	5 hrs.
Hard Dry @ 25 <sup>0</sup> C	12 hrs.
Recoating time @ 25 <sup>0</sup> C	24 hrs

*The above information is given to the best of our knowledge based on laboratory test and practical experience. However, as the paint is often used under condition beyond our control, we cannot guarantee anything but the quality of the paint itself. We reserve the right to change the given data without prior notice.*

## Recommended System:

WOOD PRESERVATIVE	1 - 2 Coats.
Wood Stain	2 Coats.
Clear Gloss Varnish	1 - 2 Coats.
WOOD PRESERVATIVE	1 – 2 Coats.
PU or Acrylic Sealer	2 Coats.
PU or Acrylic Topcoat	2 Coats.

## Storage and Handling:

The product should be kept in accordance with national regulations. WOOD PRESERVATIVE should be kept in cool place below 25<sup>0</sup>C. Shelf life of 12 months minimum in a tightly closed container. Handle with care, stir well before use.

## Cleaning of Tools:

All tools should be cleaned with Wash Thinner or Thinner # 115 as soon as possible.

## Packing:

Available in 1lit, Usg and 20 lit Pail,

## Physiological Hazards:

WOOD PRESERVATIVE does not contain dangerous solvents, nevertheless, good ventilation in working rooms is recommended as well as the use of safety tools and equipment. WOOD PRESERVATIVE is flammable and harmful if swallowed. If contact with eyes or skin occurs, wash well with fresh water and seek immediate medical advise.

FACTORY : P.O. BOX NO: 23085,SAJAH INDUSTRIAL AREA, SHARJAH, U.A.E  
TEL : 06 – 5311777, FAX 06 - 5311330:  
SHOWROOM : P.O. BOX NO: 23085,INDUSTRIAL AREA, SHARJAH, U.A.E  
TEL : 06 – 5328533, FAX 06 - 5328610  
Website : <http://www.maspaints.com/> Email : masuae@emirates.net.ae



**D-111/2004**