



# ZINC CHROMATE PRIMER

## General Description:

ZINC CHROMATE PRIMER is formulated based on modified alkyd and Zinc Chromate Pigment; it is developed as anti – corrosive primer to prevent rust on metal surfaces.

## Advantages:

- Anti corrosion on mild atmosphere.
- Weather resistance for exterior surfaces.
- Good flow and brushability
- Easy to apply.
- Excellent build and adhesion coat in alkyd system.

## Characteristics and Physical Properties:

Colour	Zinc Yellow
Coverage	13 – 15 m <sup>2</sup> / lit.
Flash Point	39 <sup>0</sup> C
Solid Content	Approx 54% by volume
Recommended D.F.T	35 microns / coat.
Touch Dry	After 2 hrs.

## Application procedure:

- Substrate must be free from oil and other contaminants.
- Sandblasting is required is sandblasting is not possible manual wire brushing is recommended. Use deruster to remove away rust and rinse with water and let it dry.

*The above information is given to the best of our knowledge based on laboratory test and practical experience. However, as the paint is often used under condition beyond our control, we cannot guarantee anything but the quality of the paint itself. We reserve the right to change the given data without prior notice.*

- Apply 1 – 2 coats of Zinc Chromate primer by roller, brush, or spray.

## Storage:

ZINC CHROMATE PRIMER should be kept in a cool area below 25<sup>0</sup>C. Keep in tightly closed container.

## Cleaning of Tools:

All tools should be cleaned with Wash Thinner or Thinner # 155 as soon as possible.

## Packing:

Available in 4 lit. (Usg), 20 lit. (Pail) and 200 lit. (Drum)

## Physiological Hazards:

ZINC CHROMATE PRIMER does not contain dangerous solvents, nevertheless, good ventilation in working rooms is recommended as well as the use of safety tools and equipment. ZINC CHROMATE PRIMER is flammable and harmful if swallowed. If contact with eyes or skin occurs, wash well with fresh water and seek immediate medical advise.

FACTORY : P.O. BOX NO: 23085, SAJJAH INDUSTRIAL AREA, SHARJAH, U.A.E  
TEL : 06 – 5311777, FAX 06 - 5311330:  
SHOWROOM : P.O. BOX NO: 23085, INDUSTRIAL AREA, SHARJAH, U.A.E  
TEL : 06 – 5328533, FAX 06 - 5328610  
Website : <http://www.maspaints.com/> Email : masuae@emirates.net.ae



**D-111/2004**