



# BOUCLE

## General Description:

BOUCLE is based on a special resin and fillers to provide a textile or linen – like effect depending on a different choice of application. Created as an alternative in internal decoration to obtain a luminous, antique and wall paper design.

## Major Uses:

- Good adhesion properties
- Repels water vapor and humidity.
- Good thermal conductivity and anti condensation.
- Anti fungus.
- Scrub resistance.
- Good flexibility.
- Various texture patterns
- Easy to apply.

## Characteristics and Physical Properties:

Colour	luminous and natural (coloured)
Gloss	Matt
Specific Gravity	1.0 – 1.2 Kg./lit.
Coverage	1.0 – 1.5 kg/sq.m.
Shelf Life	6 months
Flash Point	above 65 <sup>0</sup> C
Wash ability	Good with water and soap
Thinning / cleaning	potable water

## Surface Preparation:

### New substrates:

- Substrate must be dry and free from any form of contaminants.
- Apply 1 – 2 coats of Mas Masonry Primer into the substrate. For gypsum and powdery surface apply 1 coat of MAS AR Primer.
- Apply Boucle as per the required design.

### Old Concrete (previously painted)

- Remove all blistered, cracked and peeled off paint from the surface.

- Penetrated paint must be cleared and treated with 3% ammonia and water.
- Glossy finish coat must be sanded.
- Apply 1 coat of Masonry Primer White before application of Boucle.

## Method of Application:

Luminous	
Mas Masonry AR Primer	One (1) coat
Mas Masonry Primer	One(1) coat
Boucle` ( luminous)	as desired

Antique Effect	
Mas Masonry AR Primer	One (1) coat
Boucle (Natural)	Linen effect
Velo	Any choice of colour

Wall Paper	
Mas Masonry Primer	One (1) coat
Boucle (Natural)	Any desired design
Mas Décor (Special)	one (1) coat

## Storage:

The product must be stored in accordance with national regulations. The product should be kept in a cool and well ventilated place, protected from heat and direct sunlight. Contents must be kept tightly closed.

## Cleaning of Tools:

All tools should be cleaned with water.

## Packing:

Available in 1Usg. and 5 Usg. Pail

## Physiological Hazards:



See Safety Indication Sheet.

## Note:

The colour in the catalogue serves only as a guidelines and we cannot guarantee the perfect reproduction of the colours.

*The above information is given to the best of our knowledge based on laboratory test and practical experience. However, as the paint is often used under condition beyond our control, we cannot guarantee anything but the quality of the paint itself. We reserve the right to change the given data without prior notice.*

FACTORY	:	P.O. BOX NO: 23085,SAJJAH INDUSTRIAL AREA, SHARJAH, U.A.E
		TEL : 06 – 5311777, FAX 06 - 5311330:
SHOWROOM	:	P.O. BOX NO: 23085,INDUSTRIAL AREA, SHARJAH, U.A.E
		TEL : 06 – 5328533, FAX 06 - 5328610
Website	:	<a href="http://www.maspaints.com/">http://www.maspaints.com/</a> Email : masuae@emirates.net.ae



**D-111/2004**