



MAS DAMASCO

General Description:

MAS DAMASCO is decorative covering for interior walls based on a special natural raw materials giving an antique look, achieving this original Damasco effect, which is specially suitable for classical as well as for modern style decoration.

The product is given a high level of breath ability, prevents mildew and fungi growth and is UV resistant.

Characteristics and Physical Properties:

Viscosity	Pasty
Thinning / Cleaning	Water
Yield	150 – 200 g./m ² .
Touch Dry	1 – 2 hrs.
Gloss	Eggshell
Shelf Life	12 Months
Application by	Brush/Roller/Trowel
Dilution	30% for primer ready to use for effect.

Surface Preparation:

- For the new concrete, it should be fully cured at least 28 days and the substance must be free from any form of contaminants.
- If old concrete, all blistered, cracks and peeled off paint should be removed.
- Penetrated paint must be cleared and treated with 3% ammonia and water.
- Glossy finish coat must be sanded.

The above information is given to the best of our knowledge based on laboratory test and practical experience. However, as the paint is often used under condition beyond our control, we cannot guarantee anything but the quality of the paint itself. We reserve the right to change the given data without prior notice.

Typical Recommended System

- Apply 1 coat of MAS Masonry AR Primer.
- Level the surface with PVA Wall Filler if necessary and sand until smooth.
- Apply 1 – 2 coats of Masonry Primer tinted with desire color.
- Apply 1 – 2 coats of MAS DAMASCO tinted and diluted with 30% with water as a base coat.
- Apply the effect coat using the explained tools and technique.

Storage:

The product must be stored in accordance with national requisitions. The product should be kept in a cool and well ventilated place, protected from heat direct sunlight, containers must be kept tightly closed.

Packing:

MAS DAMASCO is available in 1 USG and 20 LITERS PAIL

Physiological Hazards:

MAS DAMASCO does not contain solvents, nevertheless, good ventilation in working rooms is recommended as well as the use of safety tools and equipment. MAS DAMASCO is harmful if swallowed. If contact with eyes or skin occurs, wash well with fresh water and seek immediate medical advise.

FACTORY : P.O. BOX NO: 23085, SAJJAH INDUSTRIAL AREA, SHARJAH, U.A.E
TEL : 06 – 5311777, FAX 06 - 5311330:
SHOWROOM : P.O. BOX NO: 23085, INDUSTRIAL AREA - 15, SHARJAH, U.A.E
TEL : 06 – 5344880, FAX 06 - 5344774
Website : <http://www.maspaints.com/> Email : masuae@emirates.net.ae



D-111/2004