



MAS DUNE

General Description:

MAS DUNE is a water base decorative interior / exterior paints that renders professional results with simple application convenience. Unlike traditional faux finishes, MAS DUNE does not elaborate intermixing of colours, layering techniques or sophisticated equipment. Simple effortless trowelling is all that required to achieve this very exquisite effect. Due to the natural mineral – blend it provides a marmorino effect which gives an elegant finishes.

Major Uses:

Can be applied on to walls, columns, and other curved surfaces leaving a joint free finish. For external application protection coat of MAS PROTECT is required to ensure a long lasting effect.

Characteristics and Physical Properties:

Viscosity	Pasty
Specific Gravity	1.5 kg. / lit. + / - 0.05
Yield	750 – 1000 g./m ² .
Touch Dry	1 – 2 hrs.
Gloss	Matt
Shelf Life	12 Months
Application by	By Trowel
Dilution	Not required.

Surface Preparation:

Allow new masonry to dry for 14 days under normal weather conditions before painting. Treat new concrete with a neutralizer and let it dry over night before rinsing with water to remove white crystal that form on the surface. Let dry for painting. Surface to be painted should be free from oil, grease, dust, dirt, contaminants and all loose grit and mortar

The above information is given to the best of our knowledge based on laboratory test and practical experience. However, as the paint is often used under condition beyond our control, we cannot guarantee anything but the quality of the paint itself. We reserve the right to change the given data without prior notice.

If repainting, remove all loose paint, scaling, flaking and peeling paint by PAINT REMOVER, rinse and let dry.

Wooden surfaces should be sanded smooth to touch and no splinters on rough edges should remain. Dust – off surface, then wipe with clean rag.

Prime concrete with MAS PVA MASONRY PRIMER (interior), MAS ACRYLIC PRIMER WHITE (exterior) and MAS UNDERCOAT ENAMEL for wooden surfaces.

After primer application apply MAS DUNE by trowel uniformly to fully cover the surfaces. To attain a double colour effects apply another coat of desired tone by trowel and scrape by spatula to enhance the design.

Storage:

The product must be stored in accordance with national requisitions. The product should be kept in a cool and well-ventilated place, protected from heat direct sunlight; containers must be kept tightly closed.

Packing:

MAS DUNE is available in 5KG Bucket and 25 KG. PAIL

Physiological Hazards:

MAS DUNE does not contain solvents, nevertheless, good ventilation in working rooms is recommended as well as the use of safety tools and equipment. MAS DUNE is harmful if swallowed. If contact with eyes or skin occurs, wash well with fresh water and seek immediate medical advise.

FACTORY : P.O. BOX NO: 23085, SAJJAH INDUSTRIAL AREA, SHARJAH, U.A.E
TEL : 06 – 5311777, FAX 06 - 5311330:
SHOWROOM : P.O. BOX NO: 23085, INDUSTRIAL AREA – 15 , SHARJAH, U.A.E
TEL : 06 – 5344880, FAX 06 - 5344774
Website : <http://www.maspaints.com/> Email : masuae@emirates.net.ae



D-111/2004