



# TINTERS

## General Description:

TINTERS are a range of concentrated dyestuff dissolved and blended with suitable solvents to give a transparent coloristic effect without altering the natural grain / tissue of woods.

## Characteristics and Physical Properties:

Appearance	Colored Liquid
Viscosity	Low (Pourable)
Sp. Weight	0.850
Flash Point	20 <sup>0</sup> C
Storage Life	One (1) year in closed container.

## Dilution:

- Tinters are incompatible with some solvents therefore, use our recommended solvents.
- Each tinter is ready for use and can be mix to others to obtain a different shade of colour of your choice.

## Method of Application:

- Prepare well the wood to be tinted, apply by brush, spray or by cloth scrubbing.
- Let it dry for 1 – 2 hrs. prior to application of primer or sealer.

*The above information is given to the best of our knowledge based on laboratory test and practical experience. However, as the paint is often used under condition beyond our control, we cannot guarantee anything but the quality of the paint itself. We reserve the right to change the given data without prior notice.*

## Storage:

Unlimited at room temperature when packed in bottle or tank. Do not stock below 0<sup>0</sup>C.

## Cleaning of Tools:

All tools should be cleaned with Wash Thinner as soon as possible.


## Packing:

Available in 4 lit (Usg.) and 20 lit (Pail)

## Physiological Hazards:

TINTERS contains dangerous solvents. Always use protective gloves and eye goggles when handling this product. It is recommended to provide proper ventilation on a working area. If contact with skin or splash in eyes, wash with fresh water and seek medical advise.

FACTORY : P.O. BOX NO: 23085, SAJAH INDUSTRIAL AREA, SHARJAH, U.A.E  
TEL : 06 – 5311777, FAX 06 - 5311330:  
SHOWROOM : P.O. BOX NO: 23085, INDUSTRIAL AREA, SHARJAH, U.A.E  
TEL : 06 – 5328533, FAX 06 - 5328610  
Website : <http://www.maspaints.com/> Email : masuae@emirates.net.ae



**D-111/2004**