



EPOTEX HB

General Description:

EPOTEX HB is a two-component hi – build epoxy-textured paint used as an intermediate coat in epoxy texture system.

Major Uses:

For masonry and concrete walls, gypsum, bricks, steel surfaces.

Characteristics and Physical Properties:

Color	Off White
Specific Gravity	1.7
Volume Solids %	75%
Gloss	Eggshell
Viscosity	Thixotropic
Ratio	4 : 1
Coverage	1 –2 m ² / lit.
Pot Life @ 30 ⁰ C	4 hrs.
Shelf Life	12 months.

Surface Preparation:

- Surface to be painted must be clean, dry, free from oil, and other foreign matters.
- Concrete surface should be primed with Epoprime Basecoat and Epoprime HB on steel.
- EPOTEX HB can be applied by using hopper gun. The choice of nozzle size, air pressure and thinner ratio will determine the texture finish.
- If the surface is required to be “Flattened” use plastic roller, wetted with white spirit not less than 30 minutes and not more than 2 hrs. after application.

The above information is given to the best of our knowledge based on laboratory test and practical experience. However, as the paint is often used under condition beyond our control, we cannot guarantee anything but the quality of the paint itself. We reserve the right to change the given data without prior notice.

Recommended System:

Steel	
Epoprime HB	- 1 Coat.
EPOTEX HB	- At required finish.
Masdur	- 1 Coat.
Concrete	
Epoprime Basecoat	- 1 Coat.
Putty Filler (If needed)	- 1 Coat.
EPOTEX HB	- At required finish.
Masdur	- 1 Coat.

Storage:

Shelf life of 12 months minimum if stored in cool and dry area.

Thinning and Cleaning:

EPOTEX HB can be thinned down up to 20% maximum depending on the textured required. All tools and equipment should be cleaned with Wash Thinner or Thinner # 135 as soon as possible.

Packing:

Available in 4 lit. set and 20 lit. set.

Physiological Hazards:

EPOTEX HB does not contain dangerous solvents, nevertheless, good ventilation in working rooms is recommended as well as the use of safety tools and equipment. The mixture in its liquid state is flammable and harmful if swallowed. If contact with eyes occurs, cleanse with fresh water and seek medical advise.

FACTORY : P.O. BOX NO: 23085, SAJJAH INDUSTRIAL AREA, SHARJAH, U.A.E
 TEL : 06 – 5311777, FAX 06 - 5311330:
 SHOWROOM : P.O. BOX NO: 23085, INDUSTRIAL AREA, SHARJAH, U.A.E
 TEL : 06 – 5328533, FAX 06 - 5328610
 Website : <http://www.maspaints.com/> Email : masuae@emirates.net.ae



D-111/2004