



AQUAWOOD WAX STAIN (FOR EXTERIORS)

General Description:

AQUAWOOD WAX STAIN (FOR EXTERIOR) is a monocomponent water based material for outdoor application with excellent resistance to blocking and provides long term protection against fungi and mould.

Major Uses:

Wooden items for interior and exterior exposure.

Characteristics and Physical Properties:

Solids content (%)	23 ± 1
Specific gravity (kg/ltr)	1,020 ± 0,030
Viscosity FC# 4 @ 25°C	37 ± 1
Drying time (50 g/m ² at 20°C)	touch dry 1 hr recoatable 4 hrs
Drying time (50 g/m ² at 20°C)	touch dry 1 hr recoatable 4 hrs
Spreading rate (m ² /kg)	15-20 per coat, depending on wood species
Number of coats	1 -3

Available colours:

AWS 010	PINE
AWS 020	NATURAL OAK
AWS 040	OREGON PINE
AWS 060	WALNUT
AWS 070	TEAK
AWS 100	MAHOGANY
AWS 110	EBONY
AWS 140	PALISANDER

Method of Application:

Brush, Dipping, Spray

The above information is given to the best of our knowledge based on laboratory test and practical experience. However, as the paint is often used under condition beyond our control, we cannot guarantee anything but the quality of the paint itself. We reserve the right to change the given data without prior notice.

Mixing Procedure:

Ready to use. If a lighter colour is required. Blend with the clear version HI 2210

Product Characteristics:

Are wax effect waterbased wood stains which ensure wood decoration leaving its natural look

Unchanged (thin film). The special wax contained in the products gives excellent water-repellent properties.

This also gives better stability to the coated item, ensuring additional protection against the disgregating

Action of water if compared to waterbased systems with conventional protective wood stain (for example

Are suitable for protecting wood exposed to the exterior environment against attack from staining fungi

and rot. They contain transparent iron oxides (clear version excepted), which provide good light fastness

and Absorb UV rays thus protecting the wood from lignin

attack. We advise against clear only systems of exterior

exposure, as they do not Contain iron oxides and therefore do not ensure

suitable protection against UV radiation.

Use of Product:

Wood species

The most suitable timbers are spruce, pine, yellow pine, Douglas fir and hemlock, both untreated and treated.

FACTORY	:	P.O. BOX NO: 23085.SAJJAH INDUSTRIAL AREA, SHARJAH, U.A.E TEL : 06 – 5311777, FAX 06 - 5311330:
SHOWROOM	:	P.O. BOX NO: 23085.INDUSTRIAL AREA, SHARJAH, U.A.E TEL : 06 – 5328533, FAX 06 - 5328610
Website	:	http://www.maspaints.com/ Email : masuae@emirates.net.ae



D-111/2004

During impregnation phase, wood species such as oak, chestnut and iroko may suffer problems of flow due to the removal of tannin compounds commonly present in these timbers by the waterbased stain.

Sanding of the bare wood

A thorough sanding is particularly important, 150 grit sanding is recommended.

Application systems

Stains can be applied by flow coating, dipping, brushing or spraying. This last application method (Spraying) is to be used only when suitable protection and ventilation devices are used.

Application on new timbers

Carefully sand the wood, (which is to be well dried), with 150 grit sandpaper.

Apply from 1 to 3 coats, depending on the degree of exposure, with an interval between coats of 4 hours max. For longer intervals, sanding of the substrate with 280 grit sandpaper is recommended. Some sanding is recommended on the last but one coat, in order to improve the appearance. The next day, after completion, if increased water-repellence is required, carefully brush the stain, for instance with sorghum.

Drying

Drying of waterbased products must take place at temperatures above 15°C and at a relative humidity not

Exceeding 85%. Out of these limits, there is a slowing down of the drying process and formation of a softer and less resistant film. In

case the product is applied outside, avoid application in particularly humid (i.e. foggy) or cold days (less than 5-10°C).

Special Instructions

- Stir products well
- Make sure the can is well sealed
- Store above 5°C
- Use in well ventilated area
- Use in temperatures above 10°C
- Do not pour waste down sinks, drains or sewers
- Waste must be disposed of responsibly and in accordance with current legislation
- Keep out of the reach of children
- Avoid contact with skin or eyes
- In case of contact with eyes, rinse immediately with plenty of water and seek medical advice

WARNING: NATURAL RESIN ESCAPE. Many timber species, especially conifers such as pine, larch, Douglas fir and spruce, contain large Quantities of natural resin in capillaries and resin sacs near knots. It is virtually impossible to eliminate this or to use coatings to block it. Sooner or later the resin will escape, the only damage is to the appearance of the material and the quality of the film is not affected.

Physiological Hazards:

AQUAWOOD WAX STAIN do not contains solvents. Ensure proper ventilation on working areas, wear gloves and safety clothing while application. When contact with eyes, splash with fresh water and seek immediate medical advise.

The above information is given to the best of our knowledge based on laboratory test and practical experience. However, as the paint is often used under condition beyond our control, we cannot guarantee anything but the quality of the paint itself. We reserve the right to change the given data without prior notice.

FACTORY	:	P.O. BOX NO: 23085, SAJJAH INDUSTRIAL AREA, SHARJAH, U.A.E
		TEL : 06 – 5311777, FAX 06 - 5311330:
SHOWROOM	:	P.O. BOX NO: 23085, INDUSTRIAL AREA, SHARJAH, U.A.E
		TEL : 06 – 5328533, FAX 06 - 5328610
Website	:	http://www.maspaints.com/ Email : masuae@emirates.net.ae



D-111/2004