

DECORSTOF

Description – water-based DECORSTOF is a satin finish for interiors with aesthetic effect. It has been developed with the most advanced technologies to provide durability, washability and environment-friendly paints. This product is created to give new decorative solutions for interiors in order to make your environment unique for their refine elegance

Characteristics and applications – to obtain the best aesthetic effect and quality results, we suggest following our application recommendations. To provide an excellent finish, it is advisable to apply a primer coat of the same tone of DECORSTOF. It can be applied on various surfaces like concrete walls, plaster, wood panels, iron ad light alloys, etc. after previous preparation.

1. Spray DECORSTOF, keeping pressure at 2-4 atm. At a distance from the substrate of about 30-40 cm. Use a spray gun with superior tank and with a nozzle of 1.7 – 1.8 mm. Spray the first coat of DECORSTOF horizontally in the quantity of 170 – 200 gms./ sq.m. to obtain perfect covering of the base (DECORSTOF dries after 2-3 hrs. at room temperature). Spray the second coat in the quantity of 100 gms./sq.m.
2. NEW CONCRETE WALLS – the wall should be fully dry without alkaline substance and it should be smooth. Otherwise, scrape with PVA Wallfiller, then sand with 180 grit sandpaper. Apply one (1) coat of Liquifix prior to the application of DECORSTOF as described in No. 1
3. OLD WALL SURFACES – use sandpaper to remove loose paints, dust and if necessary, scrape PVA Wallfiller to even-up the surface. Apply one (1) coat of Liquifix and two (2) coats of DECORSTOF as described in No. 1
4. NEW WOOD - application of PVA Wallfiller (if necessary), then sand with 280 grit sandpaper until smooth surface is obtained. Apply one (1) coat of Liquifix and two (2) coats of DECORSTOF with an interval of 5-6 hours at room temperature as described in no. 1.
5. OLD WOOD, OLD IRON – (previously painted with alkyds and P.U. paints). Smoothen with 280-300 grit sandpaper to facilitate the adhesion of Liquifix Primer and then the DECORSTOF as indicated in no. 1.
6. NEW IRON – smoothen the surface with sandpaper. Remove traces of oil, grease and other contaminants and apply one (1) coat of Deruster. Apply one (1) coat of Liquifix prior to the application of two (2) coats of DECORSTOF as mentioned in No. 1.
7. LIGHT ALLOYS – remove grease and smooth the surface and apply a coat of adequate primer. Apply one (1) coat of Liquifix before the application of DECORSTOF as described in No. 1.

Physical properties

Composition: Acrylic resins and special pigments, giving a satin finish.

Diluents: water

Specific weight: 1.100 +/- 0.100 kg./lit.

Theo. Yield: 170 – 200 gms./ sq.m.

Appearance: satin matt

Dilution: 5 – 10 % max.

Storage: keep in closed container at room temperature

Washing resistance: washes well with water or common detergents

Drying time:

Dust free: 1 hour

Touch dry: 3 hours

Hard dry: 24 hours

Stability: 6 months

Note: The information herein mentioned is given to the best of our knowledge, correct and precise and to our experience. However, the manufacturers do not assume responsibility for the effects of our recommendations or suggestions as the conditions of applications by users are beyond our control. The color in the catalogue serves only as guidelines and we cannot guarantee the perfect reproduction of the colors.