



FINISH V12

General Description:

FINISH V12 is a transparent silicon based material formulated as protection for interior and exterior decorative paint.

Major Uses:

For use as a protective coating of Décor Art to avoid fading and lime efflorescent. Wall transpiration is on the basis of DIN rule 52615 (detaching and support – sticking resistance DIN ISO 4624).

Characteristics and Physical Properties:

Color	Transparent
Specific Gravity	1.0 +/- 0.1
Flash Point	N/A
Viscosity	N/A
% Solid Content	N/A

Application Details:

Method of application	By brush , Roller
Mixing Ratio	Finish V12 : 1 Part Water : 1 Part

Surface Preparation:

- Surface must be clean, dry, free from dirt, oil, grease and other foreign matters. If detergent is used for cleaning, rinse with fresh water.
- The temperature of the substrate should be min 5⁰ C, above the dew point. Avoid painting on direct sunlight.
- Apply FINISH V12 by brush in a circular way as Décor Art.

The above information is given to the best of our knowledge based on laboratory test and practical experience. However, as the paint is often used under condition beyond our control, we cannot guarantee anything but the quality of the paint itself. We reserve the right to change the given data without prior notice.

Drying Time:

On the Surface @ 25 ⁰ C	1 hr.
Overpainting @ 25 ⁰ C	8 hrs.
Below the Surface @ 25 ⁰ C	12 hrs

Recommended System:

DÉCOR ART	2 Coats.
FINISH V12	1 Coats.

Storage and Handling:

The product should be kept in accordance with national regulations. FINISH V12 should be kept in cool place below 25⁰C. Shelf life of 12 months minimum in a tightly closed container. Handle with care, stir well before use.

Cleaning of Tools:

All tools should be cleaned with Wash Thinner or water with soaps as soon as possible.

Packing:

Available in 4KG , 20 KG.,

Physiological Hazards:

FINISH V12 does not contain solvents, nevertheless, good ventilation in working rooms is recommended as well as the use of safety tools and equipment. FINISH V12 is flammable and harmful if swallowed. If contact with eyes or skin occurs, wash well with fresh water and seek immediate medical advise.

FACTORY : P.O. BOX NO: 23085,SAJAH INDUSTRIAL AREA, SHARJAH, U.A.E
 TEL : 06 – 5311777, FAX 06 - 5311330:
 SHOWROOM : P.O. BOX NO: 23085,INDUSTRIAL AREA, SHARJAH, U.A.E
 TEL : 06 – 5328533, FAX 06 - 5328610
 Website : <http://www.maspaints.com/> Email : masuae@emirates.net.ae



D-111/2004