



FLOORCOAT AC 15

General Description:

FLOORCOAT AC 15 is a mono component sealer based on acrylic resin. It is formulated to provide an excellent bonding to all cementitious surface.

Major Uses:

To provide a sealing coat to eliminate water seepage and dust proof as well. It also serves as a concrete conditioner that reduces undercutting and peeling due to its excellent penetration, thus prevents oil and liquid absorption. Best for garage, warehouse with light traffic.

Advantages:

- Easy of apply
- Good resistance.
- Provides durable sealer.
- Dustproof when fully cured.
- Ready to use.

Characteristics and Physical Properties:

Appearance	Clear
Components	Single.
Specific Gravity	0.90
Flash Point	20 ⁰ C
Drying Time:	
Touch Dry	30 min.
Recoating Interval	2 hrs.
Hard Dry	6 hrs.
Coverage	10m ² / lit.

Surface Preparation:

New Concrete:

FLOORCOAT AC 15 can be applied by roller or spray when the surface has been dried after the finishing operation. This product does not require surface preparation and can be applied immediately onto surface. Remove all loose debris and other foreign matters prior to application.

Old Concrete:

Concrete should be free from oil, dust and other contaminants. Mechanical sanding or abrading is much preferred to obtain an effective adhesion. Any damaged areas should be repaired by using Epoxy Grout and Mortar.

Mixing and Application:

FLOORCOAT AC 15 can be applied by brush, spray or roller. Apply the material uniformly with an interval of 2 hrs. per coat. 2 – 3 coats is recommended at a rate of 10m² / lit. Coverage varies depending on the porosity of the surface. No mixing or dilution is recommended due to its ready to use viscosity.

Storage:

At least 1 year in unopened cans. The product should be stored in cool and dry area. Keep container tightly closed.

Cleaning of Tools:

All tools should be cleaned with Wash Thinner as soon as possible.

Physiological Hazards:

Keep materials away from eyes and skin contact. Good ventilation should be provided particularly in closed work areas. Keep uncured epoxy materials away from the mouth, food or drink, do not use empty tins to store food and do not empty cans into drains. Always wear gloves and safety materials when handling this product. Clean any splashes or smears from the skin immediately, using warm water and soap. Avoid inhaling vapor.

The above information is given to the best of our knowledge based on laboratory test and practical experience. However, as the paint is often used under condition beyond our control, we cannot guarantee anything but the quality of the paint itself. We reserve the right to change the given data without prior notice.

FACTORY : P.O. BOX NO: 23085, SAJAH INDUSTRIAL AREA, SHARJAH, U.A.E
TEL : 06 - 5311777, FAX 06 - 5311330:
SHOWROOM : P.O. BOX NO: 23085, INDUSTRIAL AREA, SHARJAH, U.A.E
TEL : 06 - 5328533, FAX 06 - 5328610
Website : <http://www.maspaints.com/> Email : masuae@emirates.net.ae



D-111/2004