



GRAFFITI PREVENTION

Colorless siloxane protection against graffiti, suitable for absorbent surfaces

MAS GRAFFITI PREVENTION is advised to protect any kind of surface from spray paints, enamels and from sticking up of bills, avoiding the penetration in to the pores, even if already painted with mineral absorbent finishes, and at the same time keeping constant the permeability and the aesthetic aspect of the finish.

MAS GRAFFITI PREVENTION is a siloxane product, water-based, transparent, non-flammable, and can be simply washed away by hot water.

PROPERTIES:

MAS GRAFFITI PREVENTION is marked by and stands out for the following characteristics:

- It can be applied to decorated plasters, provided surfaces are absorbent and the paints are mineral, the decoration will not be damage.
- Graffiti can be easily removed using hot water
- It does not change the water vapor permeability of the coating
- It does not change the color tone or aspect of the finishes on which is applied
- The treated surface becomes water repellent and fouling resistant
- Specific gravity : 1kg/l
- pH: 6
- Viscosity: 200 \pm 2% by weight

PURPOSES:

MAS GRAFFITI PREVENTION is particularly suitable to treat any kind of absorbent surface that can be damaged by the spray paints of graffiti.

It is possible to treat several types of surfaces, as marble, natural and artificial stone, bricks, cement, even decorated plasters, provided the surfaces are absorbent and the paints are mineral and resistant to high pressure hot water washing.

WORKING INSTRUCTIONS:

- **MAS GRAFFITI PREVENTION** is ready to use.
- It is applied by brush, two coats at least, "wet on wet"
- To ensure a perfect adhesion to backing, is advisable not to apply **MAS ALKAL 1** or **MAS ALKAL 2** is advised, according to the nature of the backing (see the respective specification sheet)
- Graffiti or similar vandal inscriptions made after the **MAS GRAFFITI PREVENTION** treatment can be easily washed away by high pressure hot water at 90 °C (194°F) and 80-100 bar
- When the graffiti have been removed, **MAS GRAFFITI PREVENTION** has to be applied to restore the former protection
- Protect eyes and skin during application
- Dispose of product with care
- Dispose of waste through authorized channels

COVERING CAPACITY:

The average spreading rate of **MAS GRAFFITI PREVENTION** is 0.3 l/ m² (TWO COATS). The spreading rate may vary according to the porosity of the surface to be treated.

An inadequate quantity of applied product may compromised the efficacy of the graffiti removal.

PACKAGING:


MAS GRAFFITI PREVENTION is available in 10l containers.

For further help or information regarding the products in the MAS range contact your local dealer.

Every care has been taken to ensure that the information in provided in this technical data sheet is accurate. Mas is unable to guarantee results as it has no control over the conditions under which its products are applied.

The above information is given to the best of our knowledge based on laboratory test and practical experience. However, as the paint is often used under condition beyond our control, we cannot guarantee anything but the quality of the paint itself. We reserve the right to change the given data without prior notice.

FACTORY : P.O. BOX NO: 23085, SAJJAH INDUSTRIAL AREA, SHARJAH, U.A.E
TEL : 06 - 5311777, FAX 06 - 5311330:
SHOWROOM : P.O. BOX NO: 23085, INDUSTRIAL AREA, SHARJAH, U.A.E
TEL : 06 - 5328533, FAX 06 - 5328610
Website : <http://www.maspaints.com/> Email : masuae@emirates.net.ae



D-111/2004