



SILV – O – LUX

General Description:

SILV – O – LUX is a brilliant, super resistant silver solution based on 100% acrylic resin with selected silver paste. It is fast drying with exceptional long lasting effect.

Major Uses:

High recommended for all decorative works on wood, metal, plaster, concrete, precast, old paint and false ceiling.

Characteristics and Physical Properties:

Color	Silver Aluminium
Specific Gravity	0.90
Solid Content	30%
Coverage	25 – 28 m ² / lit.
Dry	12 hrs.
Recotable	12 hrs.

Application Details:

Method of application	By brush, Roller or Spray
Dilution	Not required
Mixing Ratio	Single pack, Ready to use.


Surface Preparation:

Steel:

Substrate must be sandblasted to Sa2 1/2 . If sandblasting is not possible, wire blasting is recommended. The surface should be cleaned, free from dust, oil, grease and other contaminants.

The above information is given to the best of our knowledge based on laboratory test and practical experience. However, as the paint is often used under condition beyond our control, we cannot guarantee anything but the quality of the paint itself. We reserve the right to change the given data without prior notice.

FACTORY : P.O. BOX NO: 23085, SAJJAH INDUSTRIAL AREA, SHARJAH, U.A.E
TEL : 06 – 5311777, FAX 06 - 5311330:
SHOWROOM : P.O. BOX NO: 23085, INDUSTRIAL AREA, SHARJAH, U.A.E
TEL : 06 – 5328533, FAX 06 - 5328610
Website : <http://www.maspaints.com/> Email : masuae@emirates.net.ae



D-111/2004

Concrete:

Surface should be primed with adequate primer, sanded and free from foreign matters.

Wood:

Substrate should be primed with suitable primer prior to the application of SILV – O – LUX.

Storage:

SILV – O – LUX should be kept in cool area below 25⁰C.
Keep tightly closed container

Cleaning of Tools:

All tools should be cleaned with Wash Thinner or PU Thinner # 105 as soon as possible.

Packing:

Available in 1Usg, 1 lit, ½ lit and 250 ml.

Physiological Hazards:

SILV – O – LUX does not contain dangerous solvents, nevertheless, good ventilation in working rooms is recommended as well as the use of safety tools and equipment. SILV – O – LUX is flammable and harmful if swallowed. If contact with eyes or skin occurs, wash well with fresh water and seek immediate medical advise.