



# NC PUTTY # 2185 WHITE

## General Description:

N.C. PUTTY # 2185 WHITE is a special glazing based on synthetic alkyd resins, nitrocellulose and selected pigments and extenders. It is formulated to give extra body to the surface and as a levelling filler to all wooden surfaces, with a good sandable property. It gives a homogenous surface after finishing. It has good moisture resistance after drying it can withstand higher temperature up to 60°C with out any physical change.

## Major Uses:

NC PUTTY # 2185 WHITE are specially used as a levelling filler for wood and furnitures. Also as a body filler for cars and automobiles.

## Characteristics and Physical Properties:

Appearance	White Liquid
Sp. Gravity	1.20 Kg / lit.
Total Solids	69% ab
Flash Point	30°C.
Coverage / Coat	5 – 6 SQ. M. / lit. (Depending on the porosity of the surface)

## Drying Time:

Touch Dry	30 – 60 mins.
Dry to Recoat	3 – 4 hrs.
Abrasive Easiness	Sandable after 30 min.

*The above information is given to the best of our knowledge based on laboratory test and practical experience. However, as the paint is often used under condition beyond our control, we cannot guarantee anything but the quality of the paint itself. We reserve the right to change the given data without prior notice.*

## Method of Application:

- The surfaces must be primed and should be dry, clean and free of any loose particles.
- Scrape NC Putty at about 20 – 30 microns per coat (generally 2 coats or as necessary depending the smoothness of the substrate).
- Sand with sand paper prior to application of intermediate coat and topcoat.

## Storage:

Keep material in a cool place below 25°C. Keep the container tightly closed. Shelf life of 12 months minimum.

## Cleaning of Tools:

All tools should be cleaned with Wash Thinner or NC Lacquer Thinner as soon as possible.

## Packing:

Available in 1 Usg, 20 lit Pail, and 200 lit. Drum.

## Precautions:

NC PUTTY # 2185 WHITE does not contain dangerous solvents, nevertheless, good ventilation in working rooms is recommended as well as the use of safety tools and equipment. The mixture, in its liquid state is flammable and harmful if swallowed. If contact with eyes occurs, cleanse with fresh water and seek immediate medical advice.

FACTORY : P.O. BOX NO: 23085, SAJJAH INDUSTRIAL AREA, SHARJAH, U.A.E  
TEL : 06 – 5311777, FAX 06 - 5311330:  
SHOWROOM : P.O. BOX NO: 23085, INDUSTRIAL AREA, SHARJAH, U.A.E  
TEL : 06 – 5328533, FAX 06 - 5328610  
Website : <http://www.maspaints.com/> Email : masuae@emirates.net.ae



**D-111/2004**