



N.C. CRACKLED

General Description:

N.C. CRACKLED is a solution based on nitrocellulose, modified alkyd resins and selected fillers. It is developed to give a dramatic cracking effect onto the surface and it displays a very unique and antique design.

Major Uses:

For furniture's in general, cabinets, drawers, picture, frames, chairs and turned pieces.

Characteristics and Physical Properties:

Appearance	White and Clear
Specific Weight	1.2 Kg. / 1.0 kg
Flash Point	21 ⁰ C
Coverage / Coat	30 –35 m ² / gal. (Variable)

Drying Time:

Dust Free	5 – 10 min.
Set To Touch	20 – 30 min.
Piling UP	24 hrs.
Re-coated	2 – 3 hrs.

Dilution:

N.C. CRACKLED must be thinned down with 40 – 60 % N.C. thinner depending on the desired cracking effect.

Method of Application:

By Spraying (2 – 3 bar)

- The surface to be topcoated with NC Crackled should be undercoated with nitro, polyurethane, polyester primer.

The above information is given to the best of our knowledge based on laboratory test and practical experience. However, as the paint is often used under condition beyond our control, we cannot guarantee anything but the quality of the paint itself. We reserve the right to change the given data without prior notice.

- To a well – prepared surface, apply 1 coat of NC Gloss and let it dry for an hour.
- Apply uniformly NC Crackled in a single stroke process. The greater the amount of NC Crackled, the bigger the cracking effect is
- NC Crackled can be then top coated with P.U. Acrylic finish, NC Gloss Clear and NC Matt Clear.
- NC Crackled can be tinted with HD paste to attain a variety of exciting colour.

Storage:

Store in cool areas below 25⁰C. Shelf life is 12 months in closed container. Keep container tightly close.

Cleaning of Tools:

All tools should be cleaned with Wash Thinner or NC Thinner # 115 as soon as possible.

Packing:

Available in 1Usg, and 20 lit Pail.

Physiological Hazards:

NC CRACKLED does not contain dangerous solvents, nevertheless, good ventilation in working rooms is recommended as well as the use of safety tools and equipment. NC CRACKLED is flammable and harmful if swallowed, if contact with eyes occurs, cleanse with fresh water and seek immediate medical advise.

FACTORY : P.O. BOX NO: 23085, SAJJAH INDUSTRIAL AREA, SHARJAH, U.A.E
TEL : 06 – 5311777, FAX 06 - 5311330:
SHOWROOM : P.O. BOX NO: 23085, INDUSTRIAL AREA, SHARJAH, U.A.E
TEL : 06 – 5328533, FAX 06 - 5328610
Website : <http://www.maspaints.com/> Email : masuae@emirates.net.ae



D-111/2004