



NC DEAD MATT CLEAR

General Description:

NC DEAD MATT CLEAR is a glossy varnish with nitro solution, modified alkyd resin and selected fillers and additives. Suitable to woods undercoated with nitro, polyurethane, polyester and acid catalysed lacquer primers. Finished surface is very resistant to water and alcohol, hard top and sufficiently rub – resistant. It has been developed to give a brilliant finish and of great transparency.

Major Uses:

For furniture in general, chairs, turned pieces, clothes – hooks, picture moldings. Cabinets, doors etc.

Characteristics and Physical Properties:

Appearance	Opalescent
Gloss	Dead Matt
Sp. Weight	0.980 kg.
Flash Point	21 ⁰ C
Coverage/ Coat	120 – 180 gms / m ² 9 – 10 m ² / lit. @ 40 microns

Method of Application:

By spraying (3- 4 atm) / brushing

- For well prepared surface : 1 – 2 coats thinned to 60 – 100% N.C. Thinner
- Let it dry for 30 – 40 minutes, sand with fine sand paper.
- Repeat the top coating process thinned with 60 – 100% N.C. thinner to obtain the desired glossiness.

The above information is given to the best of our knowledge based on laboratory test and practical experience. However, as the paint is often used under condition beyond our control, we cannot guarantee anything but the quality of the paint itself. We reserve the right to change the given data without prior notice.

Drying Time:

Dust free	10 –15 min.
Set To Touch	30 min.
Hard To Dry	2 hrs.
Pilling Up	24 hrs.

Storage:

Keep material in a cool place below 25⁰C. Keep the container tightly closed. Shelf life of 12 months minimum.

Cleaning of Tools:

All tools should be cleaned with Wash Thinner or NC Lacquer Thinner as soon as possible.

Packing:

Available in 4 lit (Usg.), 20 lit (Pail) and 200 ltr (Drum)

Physiological Hazards:

NC DEAD MATT CLEAR does not contain dangerous solvents, nevertheless, good ventilation in working rooms is recommended as well as the use of safety tools and equipment. NC DEAD MATT CLEAR is flammable and harmful if swallowed. If contact with eyes or skin occurs, wash well with fresh water and seek immediate medical advise.

FACTORY : P.O. BOX NO: 23085, SAJJAH INDUSTRIAL AREA, SHARJAH, U.A.E
TEL : 06 – 5311777, FAX 06 - 5311330:
SHOWROOM : P.O. BOX NO: 23085, INDUSTRIAL AREA, SHARJAH, U.A.E
TEL : 06 – 5328533, FAX 06 - 5328610
Website : <http://www.maspaints.com/> Email : masuae@emirates.net.ae



D-111/2004