



NC SEMI GLOSS WHITE

General Description:

NC SEMI GLOSS WHITE is a top glossy pigmented compound, with nitro solution, modified alkyd resin and selected pigments. Suitable to woods undercoated with nitro, polyurethane, polyester primer. Final coat is resistant to water, hardtop and sufficiently rub – resistant.

Major Uses:

Furniture in general, chairs, turned pieces, picture moldings, cabinets, doors etc.

Characteristics and Physical Properties:

Appearance	White Liquid
Sp. Weight	1.08 + / - .01 kg./ lit.
Flash Point	21 ⁰ C
Coverage/ Coat	100 – 120 gms / m ² 9 –10 m ² / lit. @ 40 microns. Dft.

Method of Application:

By spraying (2, 5 –5, 6 atm) / brushing

- For all prepared woods; 1 – 2 coats of NC SEMI GLOSS WHITE thinned down with 60 – 100% N.C. Thinner.
- Let it dry, sand with fine sandpaper by manual sanding or automatic sanding machine.
- Repeat the top coating process, vertically and horizontally for a good finish.

The above information is given to the best of our knowledge based on laboratory test and practical experience. However, as the paint is often used under condition beyond our control, we cannot guarantee anything but the quality of the paint itself. We reserve the right to change the given data without prior notice.

Drying Time:

Dust free	10 –15 min.
Set To Touch	30 – 40 min.
Hard To Try	2 hrs.
Pilling Up	24 hrs.

Storage:

Keep material in a cool place below 25⁰C. Keep the container tightly closed. Shelf life of 12 months minimum.

Cleaning of Tools:

All tools should be cleaned with Wash Thinner or NC Lacquer Thinner as soon as possible.

Packing:

Available in 4 lit (Usg.), 20 lit (Pail) and 200 ltr (Drum)

Physiological Hazards:

NC SEMI GLOSS WHITE does not contain dangerous solvents, nevertheless, good ventilation in working rooms is recommended as well as the use of safety tools and equipment. NC SEMI GLOSS WHITE is flammable and harmful if swallowed. If contact with eyes or skin occurs, wash well with fresh water and seek immediate medical advise.

FACTORY : P.O. BOX NO: 23085, SAJJAH INDUSTRIAL AREA, SHARJAH, U.A.E
TEL : 06 – 5311777, FAX 06 - 5311330:
SHOWROOM : P.O. BOX NO: 23085, INDUSTRIAL AREA, SHARJAH, U.A.E
TEL : 06 – 5328533, FAX 06 - 5328610
Website : <http://www.maspaints.com/> Email : masuae@emirates.net.ae



D-111/2004