



WOOD PUTTY FILLER

General Description:

WOOD PUTTY FILLER is based on nitrocellulose solution bonded with synthetic resin and selected filler, it is developed to patch – up uneven surface of the wood and to fill holes and cracks.

Major Uses:

WOOD PUTTY FILLER can be applied over natural and synthetic wood. It is recommended for interior and exterior application.

Characteristics and Physical Properties:

Specific Weight	1 kg. / lit.
Total Solids	50 – 55%
Flash Point	20 ⁰ C

Colors Available:

- Natural
- Teak
- Light Oak
- Dark Oak
- Mahogany
- Walnut

Method of Application:

- The surface must be primed and should be clean and free from any loose particles.

The above information is given to the best of our knowledge based on laboratory test and practical experience. However, as the paint is often used under condition beyond our control, we cannot guarantee anything but the quality of the paint itself. We reserve the right to change the given data without prior notice.

- Fill the holes and cracks by scraper leave “HEAD’ to allow slight shrinkage.
- If the previous material is dry, treat the uneven surface with WOOD PUTTY FILLER.
- WOOD PUTTY FILLER should be topcoated with NC, PU or Acrylic topcoats.

Storage:

WOOD PUTTY FILLER should be kept in a cool area below 25⁰C. Keep in tightly closed container.

Cleaning of Tools:

All tools should be cleaned with Wash Thinner or NC Thinner # 115 as soon as possible.

Packing:

Available in 500 ml., 1 lit, 4 lit. (Usg), 20 lit. (Pail) and 200 lit. (Drum)

Physiological Hazards:

WOOD PUTTY FILLER does not contain dangerous solvents, nevertheless, good ventilation in working rooms is recommended as well as the use of safety tools and equipment. WOOD PUTTY FILLER is flammable and harmful if swallowed. If contact with eyes or skin occurs, wash well with fresh water and seek immediate medical advise.

FACTORY : P.O. BOX NO: 23085, SAJJAH INDUSTRIAL AREA, SHARJAH, U.A.E
TEL : 06 – 5311777, FAX 06 - 5311330:
SHOWROOM : P.O. BOX NO: 23085, INDUSTRIAL AREA, SHARJAH, U.A.E
TEL : 06 – 5328533, FAX 06 - 5328610
Website : <http://www.maspaints.com/> Email : masuae@emirates.net.ae



D-111/2004