



AMERICAN WASH

General Description:

AMERICAN WASH is a polyurethane semi – matt finish based on a polyfunctional-saturated polyesters slightly pigmented to give a coloristic effect that does not interfere on the original design of the wood.

Major Uses:

Highly recommended for household furniture such as beds, cabinets, chairs, sofas, doors and frames. For a unique finish, it is advisable to use decorative woods such as oak, sand, ash wood and the likes.

Characteristics and Physical Properties:

Color	White Transparency with different shades.
Viscosity	40 sec. FC # 4 @ 20°C
Specific Weight	0.924 Kg. / lit.
Flash Point	21°C
Drying Time	
Dust Free	15 – 17 min.
To Touch	90 min.
To pilling UP	24 hrs.
Coverage	28 – 35 m ² per gallon (approx.)

Mixing Ratio:

American Wash	100% By Volume
Catalyst # 001	50% By Volume
PU Thinner	20 – 25% By Volume

Note: It is advisable to add 4 – 5 % of Retarder Thinner in hot weather.

The above information is given to the best of our knowledge based on laboratory test and practical experience. However, as the paint is often used under condition beyond our control, we cannot guarantee anything but the quality of the paint itself. We reserve the right to change the given data without prior notice.

Application Procedure:

- The surface to be top coated must be primed by either polyurethane primer clear or polyester primer clear.
- It should be cleaned, well – sanded, free from dust, oil, water and other contaminants.
- To a well-prepared surface, apply 1 – 2 coats of the mixture, vertically and horizontally.

Storage:

Store in cool areas below 25°C. Shelf life is 12 months in closed container. Keep container tightly close.

Cleaning of Tools:

All tools should be cleaned with Wash Thinner or PU Thinner # 105 as soon as possible.

Packing:

Available in 1Usg, and 20 lit Pail.

Physiological Hazards:

AMERICAN WASH and Catalyst # 001 do not contain dangerous solvents, nevertheless, good ventilation in working rooms is recommended as well as the use of safety tools and equipment as a precaution. In case of any contact in your eyes, immediately splash it with fresh water or consult a doctor for assistance.

FACTORY : P.O. BOX NO: 23085, SAJJAH INDUSTRIAL AREA, SHARJAH, U.A.E
TEL : 06 – 5311777, FAX 06 – 5311330
SHOWROOM : P.O. BOX NO: 23085, INDUSTRIAL AREA, SHARJAH, U.A.E
TEL : 06 – 5328533, FAX 06 – 5328610
Website : <http://www.maspaints.com/> Email : masuae@emirates.net.ae



D-111/2004