



# BURL FINISH

## General Description:

Burl Effect is a special Polyurethane varnish obtained by a unique method of application of selected stain and a choice of contrast intermediate colour.

## Application Procedure:

- Surface must be primed by either polyurethane or polyester primer.
- Sand with sandpaper and apply one coat of PU Matt Hazelnut color and let it dry for about 24 hrs.
- Apply dyed walnut and keep it for 5 minutes before patching with a cloth or sponge soaked with acetone to obtained a BURL EFFECT.
- Apply 1 – 2 coats of PU Matt Clear or PU Gloss # 507 clear.

## Storage:

Store in cool areas below 25<sup>0</sup>C. Shelf life is 12 months in closed container. Keep container tightly close.

## Cleaning of Tools:

All tools should be cleaned with Wash Thinner or PU Thinner # 105 as soon as possible.

## Packing:


Available in 1Usq, and 20 lit Pail.

## Physiological Hazards:

BURL EFFECT does not contain dangerous solvents, nevertheless, good ventilation in working rooms is recommended as well as the use of safety tools and equipment as a precaution. In case of any contact in your eyes, immediately splash it with fresh water or consult a doctor for assistance.

*The above information is given to the best of our knowledge based on laboratory test and practical experience. However, as the paint is often used under condition beyond our control, we cannot guarantee anything but the quality of the paint itself. We reserve the right to change the given data without prior notice.*

FACTORY	:	P.O. BOX NO: 23085, SAJAH INDUSTRIAL AREA, SHARJAH, U.A.E TEL : 06 – 5311777, FAX 06 - 5311330:
SHOWROOM	:	P.O. BOX NO: 23085, INDUSTRIAL AREA, SHARJAH, U.A.E TEL : 06 – 5328533, FAX 06 - 5328610
Website	:	<a href="http://www.maspaints.com/">http://www.maspaints.com/</a> Email : masuae@emirates.net.ae



**D-111/2004**