



EMBOSSSED FINISH

General Description:

EMBOSSSED FINISH is one component product based on selected filing resins saturated poly functional polyester, fillers and pigments.

Major Uses:

EMBOSSSED FINISH can be used as a topcoat for obtaining its own special effect for furniture and frame.

Characteristics and Physical Properties:

Appearance	White or coloured liquid
Viscosity	35 sec # 8 fc
Flash Point	21 ⁰ C
Coverage	26 – 28 m ² / lit.

Method of Application and Usages:

- Surface to be coated must be primed with Nitro Primers, polyurethane or polyester.
- Apply by spray gun W / A nozzle in filaments and big drops and set down on the pieces with an embossing effect.
- Dilution at maximum with 5% NC Thinner.

Drying Time:

Dust free	10 min.
Hard	24 hrs.
Shelf Life	1 year in a close container.

Storage:

Store in cool areas below 25⁰C. Shelf life is 12 months in closed container. Keep container tightly close.

The above information is given to the best of our knowledge based on laboratory test and practical experience. However, as the paint is often used under condition beyond our control, we cannot guarantee anything but the quality of the paint itself. We reserve the right to change the given data without prior notice.

Cleaning of Tools:

All tools should be cleaned with Wash Thinner or PU Thinner # 105 as soon as possible.

Packing:

Available in 1Usg, and 20 lit Pail.

Physiological Hazards:

EMBOSSSED FINISH does not contain dangerous solvents, nevertheless, good ventilation in working rooms is recommended as well as the use of safety tools and equipment. EMBOSSSED FINISH is flammable and harmful if swallowed, if contact with eyes occurs, cleanse with fresh water and seek immediate medical advise.

FACTORY : P.O. BOX NO: 23085, SAJJAH INDUSTRIAL AREA, SHARJAH, U.A.E
TEL : 06 – 5311777, FAX 06 - 5311330:
SHOWROOM : P.O. BOX NO: 23085, INDUSTRIAL AREA, SHARJAH, U.A.E
TEL : 06 – 5328533, FAX 06 - 5328610
Website : <http://www.maspaints.com/> Email : masuae@emirates.net.ae



D-111/2004