



LEATHER EFFECT

General Description:

Leather Effect is based on a stained nitrocellulose lacquer with selected pigments. It is designed to provide a natural effect of brown leather. The effect may vary from small to big crack depending on the density of the applied material.

Application Procedure:

- Surface must primer by either polyurethane or polyester primer clear.
- Sanding is required before the application of dyed brown and let it dry for about 5 – 10 minutes.
- Apply 1 – 2 coats of NC Gloss # 031 Clear and keep it for 2 – 4 hrs. prior to application of cracked trans, (Leather Tinted).
- Apply 1 – 2 coats of NC Matt clear # 032 or NC Acrylic finish.

Note: *Leather Effect can be obtained as per catalogue with M.D.F. Wood.*

Storage:

Store in cool areas below 25⁰C. Shelf life is 12 months in closed container. Keep container tightly close.

Cleaning of Tools:

All tools should be cleaned with Wash Thinner or NC Thinner # 115 as soon as possible.

Packing:


Available in 1Usg, and 20 lit Pail.

Physiological Hazards:

LEATHER EFFECT does not contain dangerous solvents, nevertheless, good ventilation in working rooms is recommended as well as the use of safety tools and equipment as a precaution. In case of any contact in your eyes, immediately splash it with fresh water or consult a doctor for assistance.

The above information is given to the best of our knowledge based on laboratory test and practical experience. However, as the paint is often used under condition beyond our control, we cannot guarantee anything but the quality of the paint itself. We reserve the right to change the given data without prior notice.

FACTORY	:	P.O. BOX NO: 23085, SAJJAH INDUSTRIAL AREA, SHARJAH, U.A.E TEL : 06 – 5311777, FAX 06 - 5311330:
SHOWROOM	:	P.O. BOX NO: 23085, INDUSTRIAL AREA, SHARJAH, U.A.E TEL : 06 – 5328533, FAX 06 - 5328610
Website	:	http://www.maspaints.com/ Email : masuae@emirates.net.ae



D-111/2004