



MULTICOLOR

General Description:

MULTICOLOR is a two component polyurethane material based on poly – functional saturated polyester resin. A transparent varnish filled with selected polyester glitters of different colours that gives a unique reflection and multicolour effect.

Major Uses:

MULTICOLOR is best for cabinets, kitchen doors, chairs, and tables and also recommended for wood decors and related products.

Characteristics and Physical Properties:

Appearance	Liquid (trans.) with glitters
Sp. Weight	0.980 Kgs.
Flash Point	21 ^o C
Coverage/ Coat	8 – 10 m ² / lit.

Mixing Ratio:

MULTICOLOR	100% By Volume
Catalyst # 016	50% By Volume
PU Thinner	20 – 25% By of Volume of Total A + B mix.

Note: In hot condition, it is advisable to add 4 – 5% of retarder recommended. Before mixing multicolour, open the container and stir well settled glitters.

Method of Application and Usages:

- The surface to be top coated should be primed with polyurethane or polyester primer.

The above information is given to the best of our knowledge based on laboratory test and practical experience. However, as the paint is often used under condition beyond our control, we cannot guarantee anything but the quality of the paint itself. We reserve the right to change the given data without prior notice.

- It must be well sanded and free from dust, oil, water and contaminants.
- Apply 1 – 2 coats of intermediate coat (any choice of colour)
- Sand it carefully with fine sand paper to the extent not to damage the intermediate coat.
- Spray 1 – 2 coats of MULTICOLOR uniformly onto the surface and let it dry for an hour or two.
- Sand it gently with very fine sandpaper and apply 1 – 2 coats of PU GLOSS TAC / 033 CLEAR for a brilliant and shining finish.

Drying Time:

Dust free	15 – 17 min.
Set To Touch	90 min.
Piling UP	24 hrs.
Hard To Dry	4 hrs.

Storage:

Store in cool areas below 25^oC. Shelf life is 12 months in closed container. Keep container tightly close.

Cleaning of Tools:

All tools should be cleaned with Wash Thinner or PU Thinner # 105 as soon as possible.


Packing:

Available in 1Usg, and 20 lit Pail.

Physiological Hazards:

MULTICOLOR does not contain dangerous solvents, nevertheless, good ventilation in working rooms is recommended as well as the use of safety tools and equipment. MULTICOLOR is flammable and harmful if swallowed, if contact with eyes occurs, cleanse with fresh water and seek immediate medical advise.

FACTORY : P.O. BOX NO: 23085, SAJJAH INDUSTRIAL AREA, SHARJAH, U.A.E
TEL : 06 – 5311777, FAX 06 - 5311330:
SHOWROOM : P.O. BOX NO: 23085, INDUSTRIAL AREA, SHARJAH, U.A.E
TEL : 06 – 5328533, FAX 06 - 5328610
Website : <http://www.maspaints.com/> Email : masuae@emirates.net.ae



D-111/2004