



N.C. CRACKLED EFFECT

General Description:

N.C. CRACKLED EFFECT is a solution based on nitrocellulose, modified alkyd resins selected fillers. It is developed to give a dramatic cracking effect onto the surface and it displays a very unique and antique design.

Major Uses:

For furniture's in general, cabinets, drawers, picture, frames, chairs and turned pieces.

Characteristics and Physical Properties:

Appearance	White liquid
Specific Weight	0.95 – 1.0 Kg.
Flash Point	21 ⁰ C
Coverage / Coat	30 –35 m ² / gal. (Variable)

Drying Time:

Dust Free	5 – 10 min.
Set To Touch	20 – 30 min.
Pilling UP	24 hrs.
Re-coated	2 – 3 hrs.

Dilution:

N.C. CRACKLED EFFECT must be thinned down with 30 – 50 % N.C. thinner depending on the desired cracking effect.

Method of Application:

By Spraying (2 – 3 bar)

- The surface to be top coated with N.C. Crackled should be undercoated with nitro, polyurethane, polyester primer.

The above information is given to the best of our knowledge based on laboratory test and practical experience. However, as the paint is often used under condition beyond our control, we cannot guarantee anything but the quality of the paint itself. We reserve the right to change the given data without prior notice.

- To a well – prepared surface, apply 1 coat of N.C. Gloss and let it dry for an hour.
- Apply uniformly N.C. Crackled in a single stroke process. The greater the amount of N.C. Crackled, the bigger the cracking effect is
- Apply one more coat of N.C. Clear gloss or N.C. Clear Matt on the top of N.C. Crackled Effect.
- By varying the colour of undercoat and by adding gloss to Crackled Effect any no. of coloured crackled effect can be achieved.

Storage:

Store in cool areas below 25⁰C. Shelf life is 12 months in closed container. Keep container tightly close.

Cleaning of Tools:

All tools should be cleaned with Wash Thinner or PU Thinner # 105 as soon as possible.

Packing:

Available in 1Usg, and 20 lit Pail.

Physiological Hazards:

N.C. CRACKLED EFFECT does not contain dangerous solvents, nevertheless, good ventilation in working rooms is recommended as well as the use of safety tools and equipment. N.C. CRACKLED EFFECT is flammable and harmful if swallowed, if contact with eyes occurs, cleanse with fresh water and seek immediate medical advise.

FACTORY : P.O. BOX NO: 23085, SAJJAH INDUSTRIAL AREA, SHARJAH, U.A.E
TEL : 06 – 5311777, FAX 06 - 5311330:
SHOWROOM : P.O. BOX NO: 23085, INDUSTRIAL AREA, SHARJAH, U.A.E
TEL : 06 – 5328533, FAX 06 - 5328610
Website : <http://www.maspaints.com/> Email : masuae@emirates.net.ae



D-111/2004