



CONCRETE NEUTRALIZER

General Description:

A basic compound recommended for new plastered concrete to neutralize the acidity present in cement – concrete mixture or brought by the etching solution.

Characteristics and Physical Properties:

Appearance	Colourless Liquid
Odor	Ammoniacal
Sp. Weight	1.0
Flash Point	Not Flammable
Storage Life	One (1) year
Viscosity	15 Secs # 4 F.C

Method of Application:

CONCRETE NEUTRALIZER are normally used on a new-plastered concrete or after etching. To the new concrete, apply 1 – 2 coats of the material by roller or brush and rinse with fresh water. Before the application of primer or sealer, be sure that the surface is fully dry and free from foreign matter.

Storage:

Keep material in a cool place below 25⁰C. Keep the container tightly closed. Shelf life of 12 months minimum.

The above information is given to the best of our knowledge based on laboratory test and practical experience. However, as the paint is often used under condition beyond our control, we cannot guarantee anything but the quality of the paint itself. We reserve the right to change the given data without prior notice.

Cleaning of Tools:

All tools should be cleaned with water as soon as possible.

Packing:

Available in 4 lit (Plastic Usg.) and 20 lit (Plastic Pail)

Physiological Hazards:

CONCRETE NEUTRALIZER contains ammonia, therefore it is recommended to use safety goggles, gloves and gas mask. Avoid contact with skin that will cause irritation. If contact with eyes, splash with fresh water and seek for medical assistance.

FACTORY : P.O. BOX NO: 23085, SAJJAH INDUSTRIAL AREA, SHARJAH, U.A.E
TEL : 06 – 5311777, FAX 06 - 5311330:
SHOWROOM : P.O. BOX NO: 23085, INDUSTRIAL AREA, SHARJAH, U.A.E
TEL : 06 – 5328533, FAX 06 - 5328610
Website : <http://www.maspaints.com/> Email : masuae@emirates.net.ae



D-111/2004