



E.P. THINNER # 135

General Description:

E.P. THINNER # 135 is a clear, colorless liquid. It is a combination of alcohols, and aromatic hydrocarbon.

Major Uses:

E.P. THINNER # 135 is recommended as a solvent for epoxy paints.

Characteristics and Physical Properties:

Specific Gravity	ASTM D 3505	0.86 - 0.90 Kg. / lit.
Color (Saybolt)	ASTM D 1209	+30
Initial Boiling Point	ASTM D 850	124
Copper Corrosion	ASTM D 849	none
Non – Aromatics	ASTM D 2360	max 60%
Flash Point (Abel)	IP 170	12 ⁰ C

Storage:


Keep the container tightly closed. Shelf life is unlimited in close container. Keep away from direct sunlight and other sources of heat or ignition; do not smoke in storage areas.

Packing:

Available in 4 lit. (Usg.) 20 lit (Pail) and 200 lit (Drum)

The above information is given to the best of our knowledge based on laboratory test and practical experience. However, as the paint is often used under condition beyond our control, we cannot guarantee anything but the quality of the paint itself. We reserve the right to change the given data without prior notice.

FACTORY : P.O. BOX NO: 23085, SAJJAH INDUSTRIAL AREA, SHARJAH, U.A.E
TEL : 06 – 5311777, FAX 06 - 5311330:
SHOWROOM : P.O. BOX NO: 23085, INDUSTRIAL AREA, SHARJAH, U.A.E
TEL : 06 – 5328533, FAX 06 - 5328610
Website : <http://www.maspaints.com/> Email : masuae@emirates.net.ae



D-111/2004