



MAS ACRYLIC PRIMER

General Description:

MAS ACRYLIC PRIMER is a styrene acrylic copolymer based under coat. It has good flow and good penetration in different surfaces.

Major Uses:

For use on exterior and interior surfaces, like plaster, stucco filler, gypsum boards, concrete and asbestos cement sheeting. It is a new generation of coating that gives unmatched and long lasting maintenance free protection for all buildings. It combines both elasticity and breathing properties. While allowing moisture to escape from inside, it prevents penetration of waste and carbon dioxide from outside.

Characteristics and Physical Properties:

Colour	White
Solid (% by volume)	32%
Specific Gravity	1.35 + .02
Diluent	Water
Coverage	8 –10.5 m ² / lit. @ 30 - 35 mic. D.F.T
Drying Time at 25 ⁰ C	30min.. Touch dry – 8 hours hard dry.
Drying Time at 35 ⁰ C	20min.. Touch dry – 6 hours hard dry.
Recoating	After 8 hrs.

Application Method:

Application Method	: Brush, roller, airless or Conventional spray.
Thinner / Cleaner	: Water

The above information is given to the best of our knowledge based on laboratory test and practical experience. However, as the paint is often used under condition beyond our control, we cannot guarantee anything but the quality of the paint itself. We reserve the right to change the given data without prior notice.

If the surface needs to be prepared before painting. Application of PVA WALL FILLER to evened up the surface prior to the application of desired topcoats.

Recommended System:

MAS AR Primer	- 1 Coat.
MAS Acrylic Primer	- 1 Coat.
PVA Wall Filler	- 2 Coats.
Mastic Royal Silk / Eggshell	- 2 Coats.
Emulsion Topcoat	- 2 Coats.

Storage:

The product must be stored in accordance with national regulations. The product should be kept in a cool and well ventilated place, protected from heat and direct sunlight. Contents must be kept tightly closed.

Cleaning of Tools:

All tools should be cleaned with water.

Packing:


Available in 5 USG, 2.5 USG, 1USG and 1 ltr.

Physiological Hazards:



See Safety Indication Sheet.

FACTORY : P.O. BOX NO: 23085, SAJJAH INDUSTRIAL AREA, SHARJAH, U.A.E
TEL : 06 – 5311777, FAX 06 - 5311330:
SHOWROOM : P.O. BOX NO: 23085, INDUSTRIAL AREA, SHARJAH, U.A.E
TEL : 06 – 5328533, FAX 06 - 5328610
Website : <http://www.maspaints.com/> Email : masuae@emirates.net.ae



D-111/2004