



DURATEX FINE

General Description:

A high quality fine textured finish based on pure acrylic and selected aggregates, for interior and exterior protection and decoration. It gives long lasting and low temperature flexibility with dirt pick – up resistance on concrete gypsum, plaster and cementitious walls.

Advantages:

- Alkaline resistant.
- Water vapour permeable.
- Good weather resistance.
- Scrub resistance.
- Good adhesion, abrasion.
- Various texture patterns
- Anti – carbonation.

Characteristics and Physical Properties:

Colour	As per colour card
Gloss	Matt
Specific Gravity	1.6 +/- 0.1
Solid content	62% by volume
Coverage	2.5 sq.mt. / lit.
Touch Dry	3 hrs.
Dry to recoat	24 hrs.
Shelf Life	12 months
Flash Point	above 65 ⁰ C
Application	By roller and spatula or Trowel.
Thinning / cleaning	Water.

Surface Preparation:

New Substrates:

- Substrate must be dry and free from any form of contaminants.
- Apply 1 – 2 coats of MAS Primart – solvent diluted penetrating primer into the substrate. For gypsum and powdery surface apply 1 coat of MAS AR Primer.

The above information is given to the best of our knowledge based on laboratory test and practical experience. However, as the paint is often used under condition beyond our control, we cannot guarantee anything but the quality of the paint itself. We reserve the right to change the given data without prior notice.

- Application of 1 – 2 coats of DURATEX FINE with desired textured finish.

Old Concrete (previously painted)

- Remove all blistered, cracked and peeled off paint from the surface.
- Penetrated paint must be cleared and treated with 3% ammonia and water.
- Glossy finish coat must be sanded.
- Apply 1 coat of Masonry AR Primer and application of Primart for an optimal hiding.

Typical Recommended System:

PRIMART or MAS Masonry AR Primer-	1 coat
DURATEX FINE	- 1 coat

PRIMART or MAS Masonry AR Primer-	1 coat
DURATEX FINE	- 1 coat
Mas Velo	- 1 coat

PRIMART or MAS Masonry AR Primer-	1 coat
DURATEX FINE	- 1 coat
DURASHIELD LATEX SILK	- 1coat

Storage:

The product must be stored in accordance with national regulations. The product should be kept in a cool and well ventilated place, protected from heat and direct sunlight. Contents must be kept tightly closed.

Cleaning of Tools:

All Tools should be cleaned with water.

Packing:

Available in 1Usg. and 5 Usg. Pail

Precautions:



See Safety Indication Sheet.

FACTORY	:	P.O. BOX NO: 23085, SAJJAH INDUSTRIAL AREA, SHARJAH, U.A.E
		TEL : 06 – 5311777, FAX 06 - 5311330:
SHOWROOM	:	P.O. BOX NO: 23085, INDUSTRIAL AREA, SHARJAH, U.A.E
		TEL : 06 – 5328533, FAX 06 - 5328610
Website	:	http://www.maspaints.com/ Email : masuae@emirates.net.ae



D-111/2004