



# DURATEX SMOOTH

## General Description:

A high quality smooth and fine textured finish based on 100% acrylic resin and selected filler for interior and exterior decoration. It gives long lasting protection and low temperature flexibility that can withstand a hairline to moderate cracks.

## Major Uses:

Recommended for external use on all type of cement plaster and concrete surfaces.

## Advantages:

- Excellent colour retention.
- Excellent chalking resistance.
- Outstanding UV resistance.
- Inherent flexibility to accommodate.
- Hairline cracks in the substrate.
- Excellent dirt picks up resistance.
- Good adhesion over old and chalky substrates.
- Water vapor permeable and anti carbonation.

## Characteristics and Physical Properties:

Colour	As per color card
Gloss	Semi gloss
Specific Gravity	1.2 + / - 0.05
Solid content	40% +/- 2%
Coverage	2.5 sq.mt. / lit.
Touch Dry	1 hr.
Surface Dry	½ hr.
Full Dry	24 hrs.
Shelf Life	12 months
Flash Point	>65 <sup>0</sup> C
Application	Spray, Brush or Roller
Thinner	Water

*The above information is given to the best of our knowledge based on laboratory test and practical experience. However, as the paint is often used under condition beyond our control, we cannot guarantee anything but the quality of the paint itself. We reserve the right to change the given data without prior notice.*

## Surface Preparation:

### New Substrates:

- Substrate must be dry and free from any form of contaminants.
- Apply 1 – 2 coats of Mas Masonry Primer into the substrate. For gypsum and powdery surface apply 1 coat of MAS AR Primer.
- Apply DURATEX SMOOTH as per the required design.

### Old Concrete (previously painted)

- Remove all blistered, cracked and peeled off paint from the surface.
- Penetrated paint must be cleared and treated with 3% ammonia and water.
- Glossy finish coat must be sanded. Apply 1 coat of Masonry Primer White before application of DURATEX SMOOTH.

## Typical Recommended System:

MAS Acrylic Primer or MAS AR Primer – 1 coat.  
DURATEX SMOOTH - 2 coats.

## Storage:

The product must be stored in accordance with national regulations. The product should be kept in a cool and well ventilated place, protected from heat and direct sunlight. Contents must be kept tightly closed.

## Cleaning of Tools:

All tools should be cleaned with water.

## Packing:


Available in 1Usg. and 5 Usg. Pail

## Precautions:



See Safety Indication Sheet.

FACTORY : P.O. BOX NO: 23085, SAJJAH INDUSTRIAL AREA, SHARJAH, U.A.E  
 TEL : 06 – 5311777, FAX 06 - 5311330:  
 SHOWROOM : P.O. BOX NO: 23085, INDUSTRIAL AREA, SHARJAH, U.A.E  
 TEL : 06 – 5328533, FAX 06 - 5328610  
 Website : <http://www.maspaints.com/> Email : masuae@emirates.net.ae



**D-111/2004**