



# MAS-GRAFF

## General Description:

A high quality structured finish based on a co-polymer and selected natural stone.

## Major Uses:

For interior and exterior protection and decoration.

## Advantages:

- Alkaline resistant.
- Unsoaponifiable
- Water vapour permeable.
- Good weather resistance.
- Hides small substrate imperfections
- Good adhesion, abrasion.
- Various texture patterns
- Easy to apply.

## Characteristics and Physical Properties:

Colour	White and as per colour card
Gloss	Matt
Specific Gravity	1.9 + / - 0.1
Solid content	85% by volume
Coverage	0.5 – 1.0 sq.mt./lit.
Touch Dry	6 hrs. Depend on thickness
Dry to recoat	24 hrs.
Shelf Life	12 months
Flash Point	above 65 <sup>0</sup> C
Application	stainless steel trowel for application and plastic trowel for structuring
Thinning / cleaning	Water.

## Surface Preparation:

### New Substrates:

- Substrate must be dry and free from oil and grease.
- All dirt, laitance and other contaminants must be removed. For gypsum and powdery surface apply 1 coat of MAS AR Primer.

*The above information is given to the best of our knowledge based on laboratory test and practical experience. However, as the paint is often used under condition beyond our control, we cannot guarantee anything but the quality of the paint itself. We reserve the right to change the given data without prior notice.*

- Application of 1 coat of Mas Masonry Primer.
- Lime containing materials should be neutralized.

### Old Concrete (previously painted)

- Remove all blistered, cracked and peeled off paint from the surface.
- Penetrated paint must be cleared and treated with 3% ammonia and water.
- Glossy finish coat must be sanded.
- Apply 1 coat of Masonry AR Primer and application of Masonry Primer White for an optimal hiding.

## Method of Application:

- ❖ Apply using the stainless steel trowel in one thick coat. The grains of material will determine the thickness of the coat.
- ❖ As soon as the area of 2-4 sq.m. has been applied, structure the material using the plastic trowel, which has to be roughened before use.
- ❖ MAS-GRAFF can be applied in 3mm. And 5 mm.. thickness depending on the requirements.

## Storage:

The product must be stored in accordance with national regulations. The product should be kept in a cool and well ventilated place, protected from heat and direct sunlight. Contents must be kept tightly closed.

## Cleaning of Tools:

All Tools should be cleaned with water.

## Packing:

Available in 1Usg. and 5 Usg. Pail

## Precautions:



See Safety Indication Sheet.

FACTORY : P.O. BOX NO: 23085, SAJJAH INDUSTRIAL AREA, SHARJAH, U.A.E  
TEL : 06 – 5311777, FAX 06 - 5311330:  
SHOWROOM : P.O. BOX NO: 23085, INDUSTRIAL AREA, SHARJAH, U.A.E  
TEL : 06 – 5328533, FAX 06 - 5328610  
Website : <http://www.maspaints.com/> Email : masuae@emirates.net.ae



**D-111/2004**