



# MASGUM

## General Description:

MASGUM is a waterproofing product with a basic of elastomerized acrylic resins and additives dispersed in water. It contains special anti – fungal biocides suitable for exterior surfaces and infrequent damped areas.

## Major Uses:

Water proofing of roofs, roof coatings, expansion joints, cracks caused by periodic movements of foundations and for minor repair.

## Characteristics and Physical Properties:

|                                 |   |
|---------------------------------|---|
| Colour                          | White   |
| Specific Gravity                | 1.4   |
| %Solids (Vol.)                  | 47  |
| PVC                             | 44  |
| Flash Point                     | Water as diluent                                    |
| Ultimate Elongation             | 600%  |
| Tensile Strength                | 17 kg. / cm <sup>2</sup>                            |
| Water Vapor permeability        | 20 gm / m <sup>2</sup> (Din 53 – 122; 2mm thickness |
| Resistance to wear and tear     | Excellent   |
| Resistance to Ageing            | Excellent   |
| Resistance to Atmospheric Agent | Excellent   |

## Precautions and instruction for use:

- Prevent freezing of the product, it should be stored at a temperature not lower than 5<sup>o</sup>C.
- Carefully stir the product before use. Remove all traces of friable elements, oil, grease, plasterspots, etc. from the surfaces to be treated

*The above information is given to the best of our knowledge based on laboratory test and practical experience. However, as the paint is often used under condition beyond our control, we cannot guarantee anything but the quality of the paint itself. We reserve the right to change the given data without prior notice.*

- Apply the prime coat diluted with 50% of water.
- For the following coats, use the products in its original density or diluted with a little water and make sure that the layer has completely dried up.
- The treatment will require at least 2 kg / sq.mt. of MASGUM. In the case of particularly porous or hot surfaces, it is necessary to wet the surface before starting the treatment.

## Storage:

The product must be stored in accordance with national regulations. The product should be kept in a cool and well ventilated place, protected from heat and direct sunlight. Contents must be kept tightly closed.

## Cleaning of Tools:

All tools should be cleaned with water.

## Packing:


Available in 1Usg. and 5 Usg. Pail

## Physiological Hazards:



See Safety Indication Sheet.

FACTORY : P.O. BOX NO: 23085,SAJJAH INDUSTRIAL AREA, SHARJAH, U.A.E  
TEL : 06 – 5311777, FAX 06 - 5311330:  
SHOWROOM : P.O. BOX NO: 23085,INDUSTRIAL AREA, SHARJAH, U.A.E  
TEL : 06 – 5328533, FAX 06 - 5328610  
Website : <http://www.maspaints.com/> Email : masuae@emirates.net.ae



**D-111/2004**