



MASGUM AF

General Description:

MASGUM AF is a waterproofing product based on elastomerized acrylic resins and additives dispersed in water. It contains special anti – fungal biocides suitable for exterior surfaces and infrequent damped areas.

Major Uses:

Water proofing of roofs, expansion joints, cracks caused by periodic movements of foundations and for minor repair. Suitable for use as a damp proof membrane on all wet areas such as walls where concrete surface cracking may occur.

Characteristics and Physical Properties:

Colour	White
Specific Gravity	1.4 +/- 0.1
% Solids (Vol.)	47
PVC	44
Flash Point	Water as diluent
Ultimate Elongation	600%
Tensile Strength	17 kg. / cm ²
Water Vapor permeability	20 gm / m ² (Din 53 – 122; 2mm thickness)
Resistance to wear and tear	Excellent
Resistance to Ageing	Excellent
Resistance to Atmospheric Agent	Excellent

Precautions and instruction for use:

- Prevent freezing of the product, it should be stored at a temperature not lower than 5⁰C.
- Carefully stir the product before use. Remove all traces of friable elements, oil, grease, plasterspots, etc. from the surfaces to be treated

The above information is given to the best of our knowledge based on laboratory test and practical experience. However, as the paint is often used under condition beyond our control, we cannot guarantee anything but the quality of the paint itself. We reserve the right to change the given data without prior notice.

- Apply the prime coat diluted with 50% of water.
- For the following coats, use the products in its original density or diluted with a little water and make sure that the layer has completely dried up.
- The treatment will require at least 2 kg / sq.mt. of MASGUM AF . In the case of particularly porous or hot surfaces, it is necessary to wet the surface before starting the treatment.

Storage:

The product must be stored in accordance with national regulations. The product should be kept in a cool and well ventilated place, protected from heat and direct sunlight. Contents must be kept tightly closed.

Cleaning of Tools:

All tools should be cleaned with water.

Packing:

Available in 5 kg.. and 25 kg. Pail

Physiological Hazards:



See Safety Indication Sheet.

FACTORY : P.O. BOX NO: 23085, SAJJAH INDUSTRIAL AREA, SHARJAH, U.A.E
TEL : 06 – 5311777, FAX 06 - 5311330:
SHOWROOM : P.O. BOX NO: 23085, INDUSTRIAL AREA, SHARJAH, U.A.E
TEL : 06 – 5328533, FAX 06 - 5328610
Website : <http://www.maspaints.com/> Email : masuae@emirates.net.ae



D-111/2004