



MASTIC ROYAL (ANTI FUNGAL)

General Description:

MASTIC ROYAL (ANTI FUNGAL) is acrylic copolymer based emulsion paint with outstanding washability and outdoor durability. It has good flow and gives a smooth silky / eggshell, semi gloss and gloss finish, and contains anti bacterial and anti fungal component

Major Uses:

For use on interior surfaces, like plaster, stucco filler, gypsum boards, concrete and asbestos cement sheeting. MASTIC ROYAL (ANTI FUNGAL) is highly recommended for hospitals and public places, due to its active ingredients which exhibits extremely low water solubility and ensures long lasting protection against mildew and fungus. The active ingredients in MASTIC ROYAL (ANTI FUNGAL) meet the requirements of the XIVth and XXXVIth recommendations of the German Board of Health.

Characteristics and Physical Properties:

Colour	More than 4000 colours can be tinted.
Gloss	Silk / Semi gloss / Gloss
Solid (% by volume)	44 + 1
Specific Gravity	1.25 - 1.35
Diluent	Water
Coverage	6 – 8 m ² / lit. at 60 / 70 micron D.F.T
Drying Time at 23 ⁰ C	30mts. Touch dry – 8 hours hard dry.
Drying Time at 35 ⁰ C	20mts. Touch dry – 6 hours hard dry.

The above information is given to the best of our knowledge based on laboratory test and practical experience. However, as the paint is often used under condition beyond our control, we cannot guarantee anything but the quality of the paint itself. We reserve the right to change the given data without prior notice.

Application Method:

Application Method	Brush, roller, airless or Conventional Spray
Thinner / Cleaner	Water

If the surface needs to be prepared before painting. PVA primer and stucco for interiors only are ideal.

Recommended System:

Mas Masonry AR Primer	1 Coat.
Mas Masonry Primer White	1 Coat.
PVA Wall Filler	2 Coats.
MASTIC ROYAL (ANTI FUNGAL)	2 Coats.

Storage:

The product must be stored in accordance with national regulations. The product should be kept in a cool and well ventilated place, protected from heat and direct sunlight. Contents must be kept tightly closed.

Cleaning of Tools:

All tools should be cleaned with water.

Packing:

Available in 1Usg. and 5 Usg. Pail

Physiological Hazards:



See Safety Indication Sheet.

FACTORY : P.O. BOX NO: 23085, SAJJAH INDUSTRIAL AREA, SHARJAH, U.A.E
TEL : 06 – 5311777, FAX 06 - 5311330:
SHOWROOM : P.O. BOX NO: 23085, INDUSTRIAL AREA, SHARJAH, U.A.E
TEL : 06 – 5328533, FAX 06 - 5328610
Website : <http://www.maspaints.com/> Email : masuae@emirates.net.ae



D-111/2004