



MASTIC ROYAL SEMIGLOSS

General Description:

MASTIC ROYAL SEMIGLOSS is a semi gloss quality paint based on acrylic copolymer with outstanding washability and durability. It is formulated to give a smooth and ensures long – lasting protection against mildew and fungus.

Major Uses:

For use on exterior and interior surfaces, like concrete, plaster, stucco filler, gypsum boards and asbestos cement sheeting. It is commonly used as a topcoat in MAS Textured (Flattened) system. The active ingredients in MASTIC ROYAL SEMI GLOSS meet the requirements of XIVth and XXXVth recommendations of german board of health.

Characteristics and Physical Properties:

Colour	As per MAS Colour Card
Solid (% by volume)	32 +/- 5
Specific Gravity	1.25 + 0.05
Diluents	Water
Coverage	8 – 10 m ² / lit.
Drying Time:	
To Touch	2 hrs.
To Recoat	4 – 6 hrs.

Application Method:

Application Method	Brush, roller, airless or Conventional Spray
Thinning volume	5 – 10% of fresh water depending on the method of application.
Airless Spray	0.013” – 0.021” orifice @ 2100 psi.
Conventional Spray	50 psi pressure

The above information is given to the best of our knowledge based on laboratory test and practical experience. However, as the paint is often used under condition beyond our control, we cannot guarantee anything but the quality of the paint itself. We reserve the right to change the given data without prior notice.

Recommended System:

Mas Masonry AR Primer	1 Coat.
Mas Masonry Primer White	1 Coat.
PVA Wall Filler	2 Coats.
MASTIC ROYAL SEMIGLOSS	2 Coats.

Storage:

The product must be stored in accordance with national regulations. The product should be kept in a cool and well ventilated place, protected from heat and direct sunlight. Contents must be kept tightly closed.

Cleaning of Tools:

All tools should be cleaned with water.

Packing:


Available in 1Usg. and 5 Usg. Pail

Physiological Hazards:



See Safety Indication Sheet.

FACTORY : P.O. BOX NO: 23085,SAJJAH INDUSTRIAL AREA, SHARJAH, U.A.E
 TEL : 06 – 5311777, FAX 06 - 5311330:
 SHOWROOM : P.O. BOX NO: 23085,INDUSTRIAL AREA, SHARJAH, U.A.E
 TEL : 06 – 5328533, FAX 06 - 5328610
 Website : <http://www.maspaints.com/> Email : masuae@emirates.net.ae



D-111/2004